

View Online at <https://aerobasegroup.com/nsn/5895-01-377-0831>

Inclosure Material:

Aluminum

Overall Length:

3.480 inches

Overall Height:

3.480 inches

Overall Width:

0.750 inches

Surface Luster:

Matte

Environmental Protection:

Explosion proof and fungus proof and moisture proof and salt spray resistant and shock resistant and vibration

Vibration Resistance Range In Hertz:

+10.0/+500.0

Individual Section Quantity:

4

Vibration Resistance Amplitude:

0.06 inches total excursion

Shock Resistance Rating In Gravitational Units:

50.0

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Storage Temperature Range:

-65.0/+100.0 degrees celsius

Average Life Measurement:

Not rated

End Application:

5985-01-260-4573 as-3901/u antenna assembly

Basic Shape Style:

Rectangular or square

Maximum Operating Altitude Rating:

30000.0 feet

Inclosure Type:

Encased

Operating Control Method:

Automatic

Installation Design:

Mechanical

Control Type:

Remote

Circuit Construction Type:

Solid state

Frequency Per Channel:

50.0 megahertz output channel err-100 and 500.0 megahertz output channel err-100

Average Power Rating Per Channel:

1.0 watts input

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Receptacle, coaxial left side and receptacle, coaxial right side and solder stud bottom

Connection Contact Type And Quantity:

9 receptacle, coaxial external and 2 solder stud external

External Dc Operating Voltage In Volts:

14.8 single voltage and 15.2 single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200