## NSN 5895-01-398-1861

Frequency Mixer Stage - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-398-1861

Overall Length:
0.395 inches
Overall Diameter:
Between 0.498 inches and 0.502 inches
Environmental Protection:
Shock resistant and dustproof
Operating Tempurature Range:
-54.0/+100.0 degrees celsius
Average Life Rating:
100000.0
Storage Tempurature Range:
-65.0/+100.0 degrees celsius
Average Life Measurement:
Hours
Average Life Rating In Hours:
100000.0
End Application:
Radio receive, 50027
Basic Shape Style:
Cylindrical
Identification Designator:
M28837/9-04s-81349
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Average Power Rating Per Channel:
200.0 milliwatts input
Connection Type And Location:
Wire lead terminals bottom
Connection Contact Type And Quantity:
4 wire lead terminals external
Test Data Document:
81349-mil-m-28837 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And

81349-mil-m-28837/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

## NSN 5895-01-398-1861

Frequency Mixer Stage - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A32200