## NSN 5895-01-463-7929

Signal Data Converter - Page 1 of 2

**Overall Length:** 



View Online at https://aerobasegroup.com/nsn/5895-01-463-7929

7.750 inches
Overall Height:
0.850 inches
Overall Width:
3.000 inches
Environmental Protection:
General purpose
Operating Tempurature Range:
-20.0/+55.0 degrees celsius
Storage Tempurature Range:
-40.0/+70.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
Watkins-johnson 21.4 mhz wj receivers or other receivers with 21.4 mhz signal monitor (sm) output
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Installation Design:
Portable and top of cabinet/counter
Circuit Construction Type:
Solid state
Frequency Per Channel:
21.4 megahertz 4th input channel err-100
Signal Data Type Per Channel:
4th input channel radio frequency err-100
Connection Type And Location:
Receptacle, coaxial front and pin front and pin rear
Connection Contact Type And Quantity:
4 pin external and 2 receptacle, coaxial external
External Dc Operating Voltage In Volts:
10.0 single voltage and 16.0 single voltage
Special Features:
Manufacturer name signal monitor module; 10 mhz full span for use with 21.4 mhz if receivers; if pan display on notebook/computer; two i
inputs to connect to two receivers; dual resolution bandwidths 25 khz 8 khz; seven sweep spans; synthesized operation; user-selectable
high speed serial interface for control and data (rs-232/rs-422/rs-485); sweep and manual operation modes; 2400 to 38.4 k baud rates
Functional Description:

Collects frequency/signal strength data from the receiver sm if output and provides this data over a serial intrface to a controller such as a

N/a

Shelf Life:

**Unit Of Measure:** 

notebook personal computer

## NSN 5895-01-463-7929

Signal Data Converter - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200