## NSN 5895-01-465-3310

Power Frequency Divider-combiner - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-465-3310 **Inclosure Material:** Aluminum **Overall Length:** 4.700 inches **Overall Height:** 2.000 inches **Overall Width:** 0.500 inches **Environmental Protection:** Fungus proof and moisture proof and shock resistant and vibration **Shock Resistance Rating In Gravitational Units:** 10.0 **Operating Tempurature Range:** +32.0/+113.0 degrees fahrenheit **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 7.2 gigahertz operating channel and 8.4 gigahertz operating channel Impedance Rating Per Channel: 50.000 ohms operating channel **Shock Pulse Duration Time:** 11.0 milliseconds **Connection Type And Location:** Receptacle, power front **Connection Contact Type And Quantity:** 8 receptacle, power external **Special Features:** 8 sma female type connectors; 5-200 hz, 1.5g peak, 2-5 hz 1.0" double amplitude-vibration; 10g peak, 11ms duration, 3 axis-shock

Shelf Life: N/a

## NSN 5895-01-465-3310

Power Frequency Divider-combiner - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A32200