

View Online at https://aerobasegroup.com/nsn/5895-01-465-3310

| Inclosure Material: |
|--|
| Aluminum |
| Overall Length: |
| 4.700 inches |
| Overall Height: |
| 2.000 inches |
| Overall Width: |
| 0.500 inches |
| Environmental Protection: |
| Fungus proof and moisture proof and shock resistant and vibration |
| Shock Resistance Rating In Gravitational Units: |
| 10.0 |
| Operating Tempurature Range: |
| +32.0/+113.0 degrees fahrenheit |
| Average Life Measurement: |
| Not rated |
| Basic Shape Style: |
| Rectangular or square |
| Maximum Operating Altitude Rating: |
| 10000.0 feet |
| Inclosure Type: |
| Encased |
| Operating Control Method: |
| Automatic |
| Installation Design: |
| Mechanical |
| Circuit Construction Type: |
| Solid state |
| Frequency Per Channel: |
| 7.2 gigahertz operating channel and 8.4 gigahertz operating channel |
| Impedance Rating Per Channel: |
| 50.000 ohms operating channel |
| Shock Pulse Duration Time: |
| 11.0 milliseconds |
| Connection Type And Location: |
| Receptacle, power front |
| Connection Contact Type And Quantity: |
| 8 receptacle, power external |
| Special Features: |
| 8 sma female type connectors; 5-200 hz, 1.5g peak, 2-5 hz 1.0" double amplitude-vibration; 10g peak, 11ms duration, 3 axis-shock |
| Shelf Life: |
| N/a |

Power Frequency Divider-combiner - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A32200