

View Online at <https://aerobasegroup.com/nsn/5895-01-509-4030>

**Inclosure Material:**

Plastic

**Overall Length:**

12.000 inches

**Overall Height:**

2.500 inches

**Overall Width:**

8.000 inches

**Individual Section Quantity:**

3

**Operating Temperature Range:**

+32.0/+122.0 degrees fahrenheit

**Storage Temperature Range:**

-4.0/+158.0 degrees fahrenheit

**Basic Shape Style:**

Rectangular or square

**Inclosure Type:**

Encased

**Operating Control Method:**

Manual

**Installation Design:**

Free-standing

**Control Type:**

Local

**Operating Ac Frequency In Hertz:**

50.0 single voltage

**External Ac Operating Voltage In Volts:**

230.0 single voltage

**Special Features:**

Supports data rates up to 115.2 kbps; switches all 12 leads that are normally required for sync or async operation; compatible with dialup modems using itu-tss v.34, v.32 bis, v.32, and most other major modem standards; interfaces eia rs-232c, modular telco; data format transparent to data format; flow control transparent to flow control, but monitors/switches on dsr, cts, or rlsd, dcd; also passes or forces dtr; data rate up to rate supported by cabling; maximum distance 50 ft to any attached rs-232 device using standard cables; user controls 1 front mounted toggle switch for selecting automatic/primary/alternate; 4 internal configuration jumpers; indicators 2 front mounted leds showing active channel; connectors 3 rear mounted db25 female common, master, primary and alternate ports; consumption 8 watts; mtbf 180,000 hours; humidity tolerance 0 to 95 pct noncondensing

**Functional Description:**

Switches your data from a dedicated leased line modem to a dialup modem when leased line goes down

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**