NSN 5895-01-519-8179

Communication Equipment Interface Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5895-01-519-8179

Fragility Factor:
Rugged Storage Tempureture Bonger
Storage Tempurature Range: -40.0/+85.0 degrees celsius
·
End Application: Discrete outerwation module (dom 1) 01013 003
Discrete automation module (dam-1) 01012-003
Unpackaged Unit Length: 6.000 inches
Unpackaged Unit Width:
4.000 inches
Unpackaged Unit Height:
3.000 inches
Document Source:
09tt2
Document Type: Characteristics record
Characteristics record
Usage Design:
Rugged automation equipment for extreme environments Product Name:
Nim module (nim-1) Functional Description:
Offers high-performance logic and batch control Supplementary Features:
Facial/housing protection: nema1, 2, 4, 4x, 5, 6, 6p, 12, 12k, 13
Specification Data: 09tt2-mil-std-901d government standard and 09tt2-mil-std-167b government standard and 09tt2-mil-std-461e; featgsupports hot swapping;
redundant input and output connections; 10 digital inputs, 8 digital relay outputs; logic and batch control; unit provides convenient tag
holders that can be associated with digital readouts and push buttons - the push buttons can be configured in software to function as standard on/off switches, as toggle switches, and/or as counters; contains four user-programmable push-buttons and eight addressable
digital readouts with led status indication; fully-sealed enclosure and can operate fully submerged; powered by a 33mhz arm processor with 1mb of onboard ram and 1mb of flash memory; dam-1 embedded firmware is stored in its flash memory and is upgradeable government
standard
Shelf Life:
N/a Unit Of Measure:
Unit Of Weasure.
Domilitarization:
Demilitarization:
No Eila:
Fiig: A23800
MZJOUU