NSN 5895-01-523-4569

Signal Data Converter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5895-01-523-4569

view Offilite at https://aerobasegroup.com/hsh/soss-of-szs-4509
Operating Tempurature Range:
+0.0/+40.0 degrees celsius
Average Life Measurement:
Not rated
Basic Shape Style:
Rectangular or square
Inclosure Type:
Encased
Operating Control Method:
Automatic
Installation Design:
Rack
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
3.2 megahertz 3rd output channel err-100
Frequency Adjustment Type:
Stepped
Individual Step Frequency:
5000.0 kilohertz and 1.0 kilohertz
Variation Frequency Rating In Decibels:
-0.5 and 0.5
Attenuation In Decibels:
14.0
Impedance Rating Per Channel:
50.000 ohms operating channel
Signal Data Type Per Channel:
5th input channel pulse err-100
Connection Type And Location:
Connector, plug rear
Connection Contact Type And Quantity:
9 connector, plug external
Product Name:
If to tape/baseband converter
Special Features:
Rs-233 control; group delay equalization; compact half-rack package; input level range negative 70 dbm to 0 dbm; power 90-240 vac;
47-420 hz; 45 watts max; weight 8 lb; warran type 1 year
Functional Description:
Used to convert if to tape and record a/d signals
Shelf Life:

N/a

NSN 5895-01-523-4569

Signal Data Converter - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200