

View Online at <https://aerobasegroup.com/nsn/5895-01-539-7033>

**End Application:**

Ap-2200 (13499), rem; p/n 270-2772-030

**Special Features:**

Audio panel is available equipped with one or two modules; the two module audios are independent of each other; the audio panel can be placed in local or remote mode; receive: internally adjustable, factory preset for -20 to +12 dbm, equipped with automatic level control, 600 ohm impedance; transmit: -25 to 60 dbm, factory preset for 0 dbm on voice peaks, equipped with automatic level control, can drive 600 ohm load; connectors: headphone, microphone/ptt; audio/key lines, dc power input, recorder output; local/remote; microphone designed to operate with telex nc450d or equiv.; headset 600 ohm headphone, such as telex ph-7; loudspeaker 3" waterproof speaker, 1/2 watt rms output, min.; recorder output din connector, 3-position, with transmit & receive audio combined, output is app. -10db into hi-z load and app. -17 db into a 600 ohm load; power operates on 10.5 to 13.5 vdc, 400 ma maximum per audio module ac adapter operates on 115/230 vac (+/- 15%), 47-63 hz

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A23800