

View Online at <https://aerobasegroup.com/nsn/5895-01-559-9477>

Overall Height:

5.250 inches

Overall Width:

17.000 inches

Ac Voltage Rating:

Between 90.0 volts and 250.0 volts

Frequency Rating:

Between 47.0 hertz and 63.0 hertz

End Application:

5895-01-495-9105 - lightweight multiband satellite terminal (lmst), an/usc-6 (v) 1

Multiplexing Method:

Time division

Criticality Code Justification:

Feat

Phase:

Single

Special Features:

Electrostatic discharge sensitive (esd)

Functional Description:

Will provide the functionality for multiplexing uplink data streams and de-multiplexing downlink data streams; provides full-duplex capability and will interface the ground user equipment with the satellite modern communications and orderwire modulators and demodulators; synchronous data inputs of mixed data rates will be multiplexed into a single super-group output and sent to the satellite modern modulators for transmission; received super-groups will be received from the satellite modern demodulators and demultiplexed into their respective groups and delivered to the signal entry panel (sep) for user access; individual subscriber ports are capable of loopback in both the subscriber and aggregate direction by command through a rs-485 port

Supplementary Features:

Rack mountable in a standard 19 inch rack; item shall not exceed 25 pounds; non-oper temp -32 to +65 degrees c; non-oper altitude up to 50, 000 ft above mean sea level; oper temp 0 to +60 degrees c; oper altitude up to 8, 000 ft above mean sea level; mtbf 25, 000 hrs for a 45 degrees c ground fixed uncontrolled environment;

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T187-f