NSN 5895-01-600-0537

Signal Data Converter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5895-01-600-0537

d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Basic Shape Style: Rectangular or square nclosure Type: Encased Circuit Construction Type: Solid state Product Name: Cage: illinx hardened industrial converter Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits day connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: W/a Juit Of Measure: Demilitarization: No Filg:	Environmental Protection:
Rectangular or square nclosure Type: Encased Circuit Construction Type: Solid state Product Name: Cage: illinx hardened industrial converter Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: W/a Unit Of Measure: Demilitarization: No Filg:	Shock resistant and vibration and weatherproof
Inclosure Type: Encased Circuit Construction Type: Solid state Product Name: Cage: illinx hardened industrial converter Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Basic Shape Style:
Encased Circuit Construction Type: Solid state Product Name: Cage: illinx hardened industrial converter Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rectangular or square
Circuit Construction Type: Solid state Product Name: Cage: illinx hardened industrial converter Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	nclosure Type:
Solid state Product Name: Cage: illinx hardened industrial converter Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Encased
Product Name: Cage: illinx hardened industrial converter Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Circuit Construction Type:
Cage: illinx hardened industrial converter Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Solid state
Special Features: Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Product Name:
Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cage: illinx hardened industrial converter
d89 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rugged ip30 rated metal panel mount enclosure; rs-232 to rs-422/485 conversion; 3-way isolation, 2 k v on data ports and power circuits
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	189 connections for rs-232; terminal block connections for rs-422/485; 10-48 vdc input power; iec 60068-2-6 compliance to 4g vibrations;
N/a Unit Of Measure: Demilitarization: No Fiig:	ec 60068-2-27 compliance to 50g shocks; meets iec 61850 reqs for electrical substations
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Filig:	N/a
No Fiig:	Jnit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
	No
	Filg:
A32200	A32200