

View Online at <https://aerobasegroup.com/nsn/5905-00-001-8593>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.172 inches

**Body Diameter:**

1.078 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.172 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

1.000 inches

**Overall Diameter:**

0.875 inches

**Shaft Style:**

Round, slotted

**Contact Arm Electrical Off Position:**

Fully ccw

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Locking bushing

**Electrical Resistance Per Section:**

100.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.25 to 0.25 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0