NSN 5905-00-001-8647

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-001-8647

25.0/+25.0 Electrical Resistance: 110.000 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Independent Sealed Iterminal Type: Wire lead Reliability Indicator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Hermetically sealed Ferminal Type: Wire lead Reliability Indicator:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 nclosure Method: Hermetically sealed Ferminal Type: Wire lead Reliability Indicator:
55.0 to 175.0 nclosure Method: Hermetically sealed Ferminal Type: Wire lead Reliability Indicator:
nclosure Method: Hermetically sealed Ferminal Type: Wire lead Reliability Indicator:
Hermetically sealed Ferminal Type: Vire lead Reliability Indicator:
Terminal Type: Wire lead Reliability Indicator:
Vire lead Reliability Indicator:
Reliability Indicator:
·
Established
Reliability Failure Rate Level In Percent:
0.001
Body Diameter:
0.109 inches
Body Length:
0.250 inches
Power Dissipation Rating In Watts:
0.100 free air
Style Designator:
Axial terminal each end
Test Data Document:
31349-milr55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0