

View Online at https://aerobasegroup.com/nsn/5905-00-003-2547

## Section Quantity:

1

Body Style:

Rectangular bushing mounted

## **Reliability Indicator:**

Not established

## **Overall Length:**

1.682 inches

#### **Overall Height:**

0.470 inches

#### **Overall Width:**

0.266 inches

## Shaft Diameter:

0.100 inches

## Shaft Length:

0.250 inches

## Mounting Bushing Length:

0.250 inches

## **Body Length:**

1.312 inches

## Body Width:

0.266 inches

## **Body Height:**

0.320 inches

#### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Maximum Starting Torque:

5.00 inch-ounces

#### Screw Thread Diameter:

0.190 inches

## Screw Thread Series Designator:

Unf

# Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Lower adjacent side single row

## **Mounting Method:**

Standard bushing

## **Electrical Resistance Per Section:**

1.0 kilohms single section

# NSN 5905-00-003-2547

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:

7920.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 wire loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0