

View Online at <https://aerobasegroup.com/nsn/5905-00-003-2634>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.516 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.391 inches

Body Length:

0.500 inches

Shaft Style:

Round

Switch Type:

Rotary

Switch Voltage Rating In Volts:

120.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

312.0

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

0.245 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Switch

Electrical Resistance Per Section:

2.5 kilohms single section

Rotary Actuator Travel In Angular Deg:

312.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

5.000 ac

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0