Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-003-2981

# Section Quantity:

1

Body Style:

Rectangular w/pointer adjustment

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.187 inches

**Body Length:** 

0.312 inches

**Body Width:** 

0.500 inches

Body Height:

0.562 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Center To Center Distance Between Terminals:

0.200 inches

**Fragility Factor:** 

Delicate

**Terminal Location:** 

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

**Electrical Resistance Per Section:** 

20.000 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

320.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-5.0 to 5.0 single section

**Actuator Travel Control Feature:** 

Stops



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

### Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

#### Fiig:

A002a0