NSN 5905-00-003-7653

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-003-7653 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.500 **Overall Length:** 6.415 inches **Overall Height:** 0.375 inches **Overall Width:** 0.150 inches **Mounting Slot Width:** 0.072 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.040 inches **Body Length:** 0.375 inches **Body Width:** 0.150 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Lateral Distance Between Mounting Hole Centers:** 0.419 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:**

Slot

Electrical Resistance Per Section:

200.0 ohms single section

NSN 5905-00-003-7653

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Rotary Actuator Travel In Angular Deg: |
|--|
| 9000.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 175.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -50.0 to 50.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0 to 5.0 single section |
| Actuator Travel Control Feature: |
| Clutch |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Test Data Document: |
| 82260-8872800001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |