## NSN 5905-00-004-4973

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-004-4973 **Section Quantity: Body Style:** Cylindrical servo mounted **Pilot Diameter:** Between 0.96830 inches and 0.96880 inches Pilot Length: 0.06200 inches **Overall Length:** 2.697 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** 0.05700 inches **Body Diameter:** 1.093 inches **Shaft Diameter:** 0.1249 inches **Shaft Length:** Between 0.302 inches and 0.322 inches **Body Length:** 2.250 inches **Overall Diameter:** 1.172 inches **Mounting Lip Diameter:** 1.06200 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Double ended shaft **Shaft End Play:** 0.00400 inches **Shaft Radial Play:** 0.001 inches **Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Clamp ring

## NSN 5905-00-004-4973

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts: 2.0 free air single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 60.0 single section Special Features: Second shaft 0.125 in. Maximum Ig Terminal Type And Quantity: 12 turret Shelf Life: N/a Unit Of Measure: -- Demilitarization: No