Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-004-4975

Section Quantity: 5 **Body Style:** Cylindrical servo mounted **Pilot Diameter:** Between 0.74950 inches and 0.75000 inches **Pilot Length:** 0.06200 inches **Overall Length:** 3.435 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.05700 inches **Body Diameter:** 0.875 inches Shaft Diameter: 0.1249 inches Shaft Length: 0.500 inches **Body Length:** 1.780 inches **Overall Diameter:** 1.062 inches Mounting Lip Diameter: 0.87500 inches Mounting Lip Depth: 0.06200 inches Shaft Style: Round, slotted Shaft Bearing Type: Ball Actuator Type: Double ended shaft Shaft End Play: 0.00400 inches **Shaft Radial Play:** 0.001 inches **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Special Features:

Second shaft 0.125 in. Maximum Ig

Terminal Type And Quantity:

21 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0