## NSN 5905-00-004-5937

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-004-5937

-100.0 to 100.0  Electrical Resistance: 681.000 ohms  Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.125 inches  Body Length: 0.468 inches  Power Dissipation Rating In Watts: 0.250 free air
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Resistance Tolerance In Percent: -1.000 to 1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
-55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.125 inches  Body Length:  0.468 inches  Power Dissipation Rating In Watts:  0.250 free air
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.468 inches Power Dissipation Rating In Watts: 0.250 free air
Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.125 inches  Body Length:  0.468 inches  Power Dissipation Rating In Watts:  0.250 free air
Reliability Indicator: Not established  Body Diameter: 0.125 inches  Body Length: 0.468 inches  Power Dissipation Rating In Watts: 0.250 free air
Not established  Body Diameter:  0.125 inches  Body Length:  0.468 inches  Power Dissipation Rating In Watts:  0.250 free air
Body Diameter:  0.125 inches  Body Length:  0.468 inches  Power Dissipation Rating In Watts:  0.250 free air
0.125 inches  Body Length: 0.468 inches  Power Dissipation Rating In Watts: 0.250 free air
Body Length:  0.468 inches  Power Dissipation Rating In Watts:  0.250 free air
0.468 inches  Power Dissipation Rating In Watts:  0.250 free air
Power Dissipation Rating In Watts: 0.250 free air
0.250 free air
Ctula Dacimatav
Style Designator:
Axial terminal each end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0