NSN 5905-00-005-2489

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-005-2489 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.96880 inches Pilot Length: 0.06200 inches **Overall Length:** 1.253 inches **Undercut Diameter:** 0.975 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 0.753 inches **Overall Diameter:** 1.438 inches **Mounting Lip Diameter:** 1.06200 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:**

0.15 inch-ounces

Maximum Running Torque:

0.15 inch-ounces

NSN 5905-00-005-2489

Shaft Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.0005 inches
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50 to 0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
3 single section
Tap Location Tolerance Per Section:
-2.5/+2.5 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
90.0 single section and 180.0 single section and 270.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
90.0 single section
Test Data Document:

10001-2267384 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

5 turret

Terminal Type And Quantity:

NSN 5905-00-005-2489

Precision Wire Wound Variable Resistor - Page 3 of 3



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0