NSN 5905-00-005-2646

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-005-2646 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting hole/slot **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.074 inches **Shaft Diameter:** 0.062 inches **Shaft Length:** 0.015 inches **Body Length:** 0.375 inches **Body Width:** 0.203 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 10.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 9000.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:**

150.0 single section

Power Dissipation Rating Per Section In Watts
0.5 free air single section

Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section

Actuator Travel Control Feature:

Clutch

NSN 5905-00-005-2646

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No