Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-005-2971

## Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

## **Overall Length:**

0.394 inches

#### **Overall Height:**

0.434 inches

#### **Overall Width:**

0.341 inches

## Body Length:

0.394 inches

## Body Width:

0.206 inches

# Body Height:

0.434 inches

# Actuator Type:

Flush drive with slot-hole

## Maximum Running Torque:

5.00 inch-ounces

## Center To Center Distance Between Terminals:

0.300 inches

## **Terminal Location:**

Rear end

## **Mounting Method:**

Terminal

## **Electrical Resistance Per Section:**

500.0 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

270.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.150 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-0.1 to 0.1 single section

# Actuator Travel Control Feature:

Stops



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0