NSN 5905-00-005-3382

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-005-3382 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 0.62450 inches and 0.62500 inches Pilot Length: 0.06200 inches **Overall Length:** 1.955 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1245 inches and 0.1248 inches **Shaft Length:** 0.375 inches **Body Length:** 1.580 inches **Overall Diameter:** 1.063 inches **Mounting Lip Diameter:** 0.87500 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:**

Between 3600.0 and 3610.0 **Maximum Starting Torque:** 0.40 inch-ounces **Maximum Running Torque:** 0.30 inch-ounces

NSN 5905-00-005-3382

Maximum Stop Torque:

96.00 inch-ounces **Shaft End Play:**0.00300 inches

Precision Wire Wound Variable Resistor - Page 2 of 3



| Shaft Runout: | |
|--|--|
| 0.001 inches | |
| Lateral Runout: | |
| 0.003 inches | |
| Pilot Diameter Runout: | |
| 0.00150 inches | |
| Shaft Radial Play: | |
| 0.002 inches | |
| Terminal Location: | |
| Longitudinally positioned on the circumference | |
| Mounting Method: | |
| Clamp ring | |
| Features Provided: | |
| Grounded contact arm and nonmetallic shaft | |
| Electrical Resistance Per Section: | |
| 50.000 kilohms single section | |
| Rotary Actuator Travel In Angular Deg: | |
| Between 3600.0 and 3610.0 | |
| Function Conformity Tolerance Per Section: | |
| -0.20/+0.20 single section | |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: | |
| 125.0 single section | |
| Power Dissipation Rating Per Section In Watts: | |
| 2.5 free air single section | |
| Function Conformity Per Section: | |
| Single section independent linearity | |
| Resistance Tolerance Per Section In Percent: | |
| -3.0 to 3.0 single section | |
| Actuator Travel Control Feature: | |
| Stops | |
| Function Characteristic Per Section: | |
| Single section linear | |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: | |
| -20.0/+20.0 single section | |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: | |
| 70.0 single section | |
| Terminal Type And Quantity: | |
| 3 solder stud | |
| Shelf Life: | |
| N/a | |
| | |

NSN 5905-00-005-3382

Precision Wire Wound Variable Resistor - Page 3 of 3



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0