NSN 5905-00-005-9529

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-005-9529 **Section Quantity:** 1 **Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.760 inches **Terminal Length:** 0.125 inches **Overall Height:** 0.320 inches **Overall Width:** 0.300 inches **Body Length:** 0.760 inches **Body Width:** 0.250 inches **Body Height:** 0.195 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 6480.0 **Center To Center Distance Between Terminals:** 0.600 inches **Fragility Factor:** Moderately delicate **Terminal Location: Dual inline Mounting Method: Terminal Features Provided:** Humidity proof **Cubic Measure:** 0.037 cubic inches **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:**

6480.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

NSN 5905-00-005-9529

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0 to 100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Two wiper terminals **Precious Material And Location:** Terminal surfaces gold **Precious Material And Weight:** 0.160 gold grains, troy **Precious Material:** Gold **Terminal Type And Quantity:** 4 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:** No