Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-006-1238

Section	Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.150 inches

Shaft Diameter:

0.100 inches

Shaft Length:

0.125 inches

Body Length:

0.750 inches

Body Width:

0.160 inches

**Body Height:** 

0.300 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

7200.0

**Center To Center Distance Between Terminals:** 

0.200 inches

**Terminal Location:** 

Radially positioned over less than half the circumference

#### Mounting Method:

Terminal

**Electrical Resistance Per Section:** 

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

7200.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# NSN 5905-00-006-1238 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

1.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

# Actuator Travel Control Feature:

Continuous motion

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

#### Unit Of Measure:

---

# Demilitarization:

No

#### Fiig:

A002a0