## NSN 5905-00-006-3109

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-006-3109

**Section Quantity: Body Style:** Rectangular, open element **Reliability Indicator:** Not established **Terminal Length:** 0.125 inches **Body Length:** 0.150 inches **Body Width:** 0.394 inches **Body Height:** 0.394 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Maximum Running Torque:** 4.20 inch-ounces **Maximum Stop Torque:** 7.00 inch-ounces **Center To Center Distance Between Terminals:** 0.125 inches **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 235.0 and 245.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.125 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 70.0 single section **Power Dissipation Rating Per Section In Watts:** 0.1 free air single section **Resistance Tolerance Per Section In Percent:** -20.0 to 20.0 single section

**Actuator Travel Control Feature:** 

Stops

## NSN 5905-00-006-3109

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
|---|
| 40.0 single section   |
| Standard Taper Curve Per Section:                                   |
| A single section  |
| Terminal Type And Quantity:   |
| 3 pin   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |