NSN 5905-00-006-5549

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-006-5549 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Terminal Length:** 0.300 inches **Mounting Hole Diameter:** 0.062 inches **Shaft Diameter:** 0.060 inches **Shaft Length:** 0.040 inches **Body Length:** 0.375 inches **Body Width:** 0.150 inches **Body Height:** 0.375 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Center To Center Distance Between Terminals:** 0.200 inches **Lateral Distance Between Mounting Hole Centers:** 0.419 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 500.000 ohms single section **Rotary Actuator Travel In Angular Deg:**

7920.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-00-006-5549

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0