

View Online at <https://aerobasegroup.com/nsn/5905-00-006-7099>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-30.0 to 30.0

**Electrical Resistance:**

56.200 ohms

**Resistance Tolerance In Percent:**

-1.000 to 1.000

**Ambient Temperature In Deg Celsius At Full Rated Power:**

25.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

275.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0 to 275.0

**Inclosure Method:**

Encased

**Terminal Type:**

Tab, solder lug

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.010

**Terminal Length:**

Between 0.376 inches and 0.500 inches

**Body Length:**

Between 1.000 inches and 1.124 inches

**Body Width:**

Between 0.469 inches and 0.593 inches

**Body Height:**

Between 0.531 inches and 0.593 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 0.709 inches and 0.729 inches

**Power Dissipation Rating In Watts:**

8.000 free air

**Err Default:**

0.140 inches

**Mounting Hole Size:**

Between 0.120 inches and 0.130 inches

**Cubic Measure:**

0.395 cubic inches

**Unpackaged Unit Weight:**

16.5 grams

**Style Designator:**

Axial terminal (s)

**Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-r-39009/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A001a0