NSN 5905-00-006-7385

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-006-7385 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.300 inches **Overall Height:** 0.315 inches **Overall Width:** 0.275 inches **Mounting Hole Diameter:** 0.093 inches **Shaft Diameter:** 0.050 inches **Shaft Length:** 0.125 inches **Body Length:** 1.250 inches **Body Width:** 0.275 inches **Body Height:** 0.315 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 7920.0 **Maximum Starting Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:**

Features Provided:Nonmetallic shaft

Unthreaded hole

NSN 5905-00-006-7385

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0 to 50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0