NSN 5905-00-006-8845

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-006-8845

Electrical Resistance: 80.000 kilohms Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Incoparature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+100.0 Inclosure Method: Incoparatiand Incop	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+100.0 Inclosure Method: 155.0/+100.0 Inclosure Method: 156.0/+100.0 Inclosure	-5.0/+5.0
Resistance Tolerance in Percent: 1.000 to 1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient in Deg Celsius: 155.0/+100.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 300dy Diameter: 10.125 inches 300dy Diameter: 10.125 inches 7-ower Dissipation Rating in Watts: 10.100 free air Skyle Designator: Avial terminal each end Fest Data Document: 105424-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Via Junt Of Messure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+100.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.125 inches Body Length: 1.375 inches Power Dissipation Rating In Watts: 1.010 free air Style Designator: Avial terminal each end Test Data Document: 155424-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: 146 1476 Measure: 1470 - Permilitarization: 1470 - Permilitarization: 1470 - Permilitarization: 1471 - Permilitarization:	60.000 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.125 inches Body Length: 2.375 inches Power Dissipation Rating In Watts: 1.010 free air Style Designator: Xixial terminal each end Test Data Document: 9542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Juint Of Measure: - Demilitarization: No Policy Company Comp	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+100.0 Inclosure Method: Incapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 3040 Plameter: 20.125 inches Power Dissipation Rating In Watts: 20.125 inches Power Dissipation Rating In Watts: 20.126 for ea in Style Designator: Axial terminal each end Fest Data Document: 205542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Ditt Of Measure: - Demilitarization: No	-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+100.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.0125 inches Power Dissipation Rating In Watts: 1.0100 free air Style Designator: Axial terminal each end Test Data Document: 195542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Juit Of Measure: - Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Pempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+100.0 nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: xixial terminal each end Fest Data Document: 95842-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Julit Of Measure: Demilitarization: No Performance requirements and test conditions that are shown as "typical", "average", "", etc.).	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+100.0 nclosure Method: ncapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 95542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No Figig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Diameter: 0.125 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Avial terminal each end Fest Data Document: 95542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formative excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Juit Of Measure: - Demilitarization: No Filig:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 95542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Juit Of Measure: - Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 95542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Fig:	-55.0/+100.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Avial terminal each end Fest Data Document: 95542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Perilig:	Inclosure Method:
Action in the lead Reliability Indicator: Not established Body Diameter: 0.125 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Avial terminal each end Fest Data Document: 05542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: - Demilitarization: No	Encapsulated
Reliability Indicator: Not established Body Diameter: D.125 inches Body Length: D.375 inches Power Dissipation Rating In Watts: D.100 free air Style Designator: Axial terminal each end Fest Data Document: D5542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Terminal Type:
Note established Body Diameter: Diagonia Diameter: Diagonia Diameter: Diagonia Document: Diagonia Doc	Wire lead
Sody Length: 0.125 inches 30dy Length: 0.375 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 0.5542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Reliability Indicator:
20.125 inches 20.375 inches 20	Not established
Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 05542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 0.5542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formate excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Junit Of Measure: - Demilitarization: No	0.125 inches
Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 0.5542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fig:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: 95542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:	0.375 inches
Style Designator: Axial terminal each end Fest Data Document: 95542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation form	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 05542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.100 free air
Test Data Document: 05542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Style Designator:
25542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	95542-137-578 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: - Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization: No -	Shelf Life:
- Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
	Fiig:
\001a0	A001a0