

View Online at <https://aerobasegroup.com/nsn/5905-00-007-0036>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.955 inches

**Body Diameter:**

1.437 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.440 inches

**Mounting Bushing Length:**

0.380 inches

**Body Length:**

2.000 inches

**Overall Diameter:**

1.686 inches

**Undercut Diameter:**

0.125 inches

**Shaft Style:**

Round, stepped

**Shaft Bearing Type:**

Ball

**Contact Arm Electrical Off Position:**

Fully cw

**Actuator Type:**

Dual concentric

**Effective Electrical Rotation In Deg Angular Rotation:**

354.0

**Maximum Starting Torque:**

0.30 inch-ounces

**Maximum Running Torque:**

0.20 inch-ounces

**Nonturn Device Location:**

At 6 oclock

**Nonturn Device Radius:**

0.432 inches

**Shaft End Play:**

0.00100 inches

**Shaft Runout:**

0.00100 inches

**Shaft Radial Play:**

0.001 inches

**Undercut Length:**

0.440 inches

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

10.000 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.50 to 0.50 all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Power Dissipation Rating Per Section In Watts:**

4.0 free air all sections

**Function Conformity Per Section:**

All sections independent linearity

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

All sections linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 all sections

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0