Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-007-3835

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Body Length:

0.750 inches

Body Width:

0.250 inches

Body Height:

0.165 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

7200.0

Terminal Location:

Dual inline

Mounting Method:

Terminal

Electrical Resistance Per Section:

2.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

7200.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin clamp

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0