

View Online at <https://aerobasegroup.com/nsn/5905-00-007-3935>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**First Flat Length:**

Between 0.175 inches and 0.195 inches

**Flat Height:**

Between 0.083 inches and 0.103 inches

**Shaft Diameter:**

Between 0.146 inches and 0.166 inches

**Shaft Length:**

Between 0.695 inches and 0.715 inches

**Body Length:**

Between 0.380 inches and 0.410 inches

**Body Width:**

Between 0.568 inches and 0.588 inches

**Body Height:**

Between 0.740 inches and 0.760 inches

**Shaft Style:**

Round, parallel flatted

**Actuator Type:**

Double ended shaft

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Terminal

**Cubic Measure:**

0.183 cubic inches

**Electrical Resistance Per Section:**

250.0 kilohms single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

20.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0