NSN 5905-00-007-3935

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-007-3935

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
First Flat Length:
Between 0.175 inches and 0.195 inches
Flat Height:
Between 0.083 inches and 0.103 inches
Shaft Diameter:
Between 0.146 inches and 0.166 inches
Shaft Length:
Between 0.695 inches and 0.715 inches
Body Length:
Between 0.380 inches and 0.410 inches
Body Width:
Between 0.568 inches and 0.588 inches
Body Height:
Between 0.740 inches and 0.760 inches
Shaft Style:
Round, parallel flatted
Actuator Type:
Double ended shaft
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Terminal
Cubic Measure:
0.183 cubic inches
Electrical Resistance Per Section:
250.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
20.0 free air single section
Resistance Tolerance Per Section In Percent:
-30.0 to 30.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section

NSN 5905-00-007-3935

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0