NSN 5905-00-007-7274

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-007-7274

| 7.0 to 7.0 Electrical Resistance: 3.100 kilohms Resistance Tolerance in Percent: 0.100 to 0.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0 to 125.0 Tempurature Range Of | Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|--|--|
| Resistance Tolerance In Percent: 0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Tersi Data Document: 15569-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | 7.0 to 7.0 |
| Resistance Tolerance In Percent: 0.100 to 0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wife lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Tersi Data Document: 05899-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via | Electrical Resistance: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Info: 175.0 Info: 175.0 Info: 175.0 Inclosure Method: Incapsulated Iteminal Type: Wire lead Reliability Indicator: Not established Body Length: 10.295 inches 10.295 inches 10.300 inches 10.400 | 9.100 kilohms |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.302 inches Body Width: 0.100 inches Power Dissipation Rating In Watts: 0.300 ree air Style Designator: Terminals one edge Test Data Document: 15869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | Resistance Tolerance In Percent: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 05696-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wie | 0.100 to 0.100 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30dy Length: 0.295 inches 30dy Width: 0.320 inches 30dy Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | Ambient Tempurature In Deg Celsius At Full Rated Power: |
| Interport and the property of | 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.3300 free air Style Designator: Terminals one edge Test Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 105869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | 175.0 |
| Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Note established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | Fempurature Range Of Tempurature Coefficient In Deg Celsius: |
| Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 0.5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | 55.0 to 125.0 |
| Terminal Type: Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | nclosure Method: |
| Wire lead Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | Encapsulated |
| Reliability Indicator: Not established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 0.5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a | Ferminal Type: |
| Note established Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a | Nire lead |
| Body Length: 0.295 inches Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | Reliability Indicator: |
| Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Ferminals one edge Fest Data Document: 0.5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa | Not established |
| Body Width: 0.320 inches Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a | Body Length: |
| D.320 inches Body Height: D.100 inches Power Dissipation Rating In Watts: D.300 free air Style Designator: Terminals one edge Test Data Document: D5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a |).295 inches |
| Body Height: 0.100 inches Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a | 3ody Width: |
| D.100 inches Power Dissipation Rating In Watts: D.300 free air Style Designator: Terminals one edge Test Data Document: D5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a |).320 inches |
| Power Dissipation Rating In Watts: 0.300 free air Style Designator: Terminals one edge Test Data Document: 0.5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a | 3ody Height: |
| O.300 free air Style Designator: Terminals one edge Test Data Document: O5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: | 0.100 inches |
| Style Designator: Terminals one edge Test Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: | Power Dissipation Rating In Watts: |
| Test Data Document: D5869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a | 0.300 free air |
| Test Data Document: 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a | Style Designator: |
| 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a | Γerminals one edge |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a | Геst Data Document: |
| Shelf Life: N/a | 05869-719260 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| N/a | excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| | Shelf Life: |
| Jnit Of Measure: | √la |
| - | Jnit Of Measure: |
| | - |
| Demilitarization: | Demilitarization: |
| No | No |
| Filg: | Filg: |
| A001a0 | A001a0 |