Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-007-7386

# Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

# Reliability Indicator:

Not established

### **Overall Length:**

0.810 inches

#### **Terminal Length:**

0.200 inches

#### **Overall Height:**

0.560 inches

#### Overall Width:

0.190 inches

#### Shaft Diameter:

# 0.100 inches

Shaft Length:

# 0.060 inches

Body Length:

# 0.750 inches

Body Width:

# 0.190 inches

# Body Height:

0.360 inches

#### Shaft Style:

Round

# Actuator Type:

Single shaft

# Center To Center Distance Between Terminals:

0.500 inches

# Lateral Distance Between Mounting Hole Centers:

0.500 inches

#### **Terminal Location:**

Dual inline

# **Mounting Method:**

Terminal

# Center To Center Distance Between Terminal Rows:

0.100 inches

#### **Electrical Resistance Per Section:**

5.0 kilohms single section

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.200 inches



# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:105.0 single sectionTempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:-100.0 to 100.0 single sectionPower Dissipation Rating Per Section In Watts:0.75 free air single sectionResistance Tolerance Per Section In Percent:-10.0 to 10.0 single sectionAmbient Tempurature In Deg Celsius Per Section At Full Rated Power:25.0 single sectionStandard Taper Curve Per Section:A single sectionTerminal Type And Quantity:3 pinShelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0