NSN 5905-00-008-0800

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-008-0800 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 3.500 inches **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 2.500 inches **Overall Diameter:** 1.750 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location: Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 20.0 kilohms single section

NSN 5905-00-008-0800

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-25.0 to 25.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Resistance Tolerance Per Section In Percent:
-2.0 to 2.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No