NSN 5905-00-008-0943

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-008-0943 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.579 inches **Body Diameter:** 1.859 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.813 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.766 inches **Overall Diameter:** 2.063 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 275.0 **Fragility Factor:** Moderately delicate **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:**

Humidity proof

Electrical Resistance Per Section:

500.000 ohms single section

NSN 5905-00-008-0943

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Rotary Actuator Travel In Angular Deg: |
|--|
| 295.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 85.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 4.000 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.000 to 10.000 single section |
| Actuator Travel Control Feature: |
| Stops |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| -20.0 to 20.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 40.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |