## NSN 5905-00-008-1638

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-008-1638 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.000 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.500 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.500 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Fragility Factor:** Rugged **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Features Provided:** Shaft seal **Cubic Measure:** 0.098 cubic inches

Electrical Resistance Per Section: 1.000 kilohms single section

## NSN 5905-00-008-1638

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0 to 20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

\_\_\_\_\_

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A002a0