## NSN 5905-00-008-2488

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-008-2488 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.406 inches **Body Diameter:** 0.515 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.406 inches **Body Length:** 0.562 inches **Overall Diameter:** 0.515 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 0.25 inch-ounces **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** 

Locking bushing

**Electrical Resistance Per Section:** 

350.000 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

300.0

## NSN 5905-00-008-2488

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Power Dissipation Rating Per Section In Watts: 7.5 heat sink single section Resistance Tolerance Per Section In Percent: -10.0 to 10.0 single section Actuator Travel Control Feature: Stops Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: -Demilitarization:

No Fiig: A002a0