

View Online at <https://aerobasegroup.com/nsn/5905-00-008-6871>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.297 inches

Terminal Length:

0.164 inches

Body Diameter:

0.766 inches

Shaft Diameter:

0.126 inches

Shaft Length:

0.906 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.391 inches

Overall Diameter:

0.930 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.391 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing w/panel seal

Electrical Resistance Per Section:

25.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

13993-st32014 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0