NSN 5905-00-008-8284

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-008-8284

| Section Quantity: |
|---|
| 1 |
| |
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Shaft Diameter: |
| 0.070 inches |
| Shaft Length: |
| 0.040 inches |
| Body Length: |
| 0.270 inches |
| Body Width: |
| 0.170 inches |
| Body Height: |
| 0.250 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Maximum Starting Torque: |
| 3.00 inch-ounces |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Features Provided: |
| Nonmetallic shaft |
| Electrical Resistance Per Section: |
| 500.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 4320.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 175.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -100.0 to 100.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.25 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0 to 10.0 single section |
| Actuator Travel Control Feature: |
| Clutch |

NSN 5905-00-008-8284

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

