NSN 5905-00-009-1129

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-009-1129 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.9970 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.997 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 1.100 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.620 inches **Body Length:** 0.812 inches **Mounting Lip Diameter:** 1.1000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Effective Electrical Rotation In Deg Angular Rotation:**

Actuator Type: Single shaft 260.0 **Maximum Starting Torque:** 0.30 inch-ounces **Maximum Running Torque:** 0.30 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches

NSN 5905-00-009-1129

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.15
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-2.00 to 2.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-500.0/+500.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
1.0 free air single section Function Conformity Per Section:
-
Function Conformity Per Section:
Function Conformity Per Section: Single section absolute linearity
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent:
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature:
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section:
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity:
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 wire lead
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 wire lead Shelf Life:
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 wire lead Shelf Life: N/a
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 wire lead Shelf Life: N/a
Function Conformity Per Section: Single section absolute linearity Resistance Tolerance Per Section In Percent: -10.0/+10.0 single section Actuator Travel Control Feature: Continuous motion Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity: 3 wire lead Shelf Life: N/a Unit Of Measure:

A002a0