Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-009-2974

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Overall Length:**

2.644 inches

#### **Body Diameter:**

0.875 inches

Shaft Diameter:

0.249 inches

Shaft Length:

Between 0.375 inches and 0.812 inches

#### Mounting Bushing Length:

0.250 inches

# **Body Length:**

1.457 inches

#### **Overall Diameter:**

1.188 inches

#### Shaft Style:

Round

#### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Double ended shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

0.60 inch-ounces

#### Maximum Running Torque:

0.60 inch-ounces

#### Maximum Stop Torque:

128.00 inch-ounces

# Shaft End Play:

0.0085 inches

#### Shaft Runout:

0.001 inches

## Lateral Runout:

0.003 inches

## **Pilot Diameter Runout:**

0.00100 inches



Shaft Radial Play:	
0.003 inches	
Screw Thread Diameter	
0.375 inches	
Screw Thread Series De	signator:
Unef	
Screw Thready Qty Per	Inch (tpi):
32.0	
Terminal Location:	
_ongitudinally positioned	on the circumference
Mounting Method:	
Standard bushing	
Electrical Resistance Pe	r Section:
10.0 kilohms single sectio	n
Rotary Actuator Travel I	n Angular Deg:
3600.0	
Function Conformity To	lerance Per Section:
0.25/+0.25 single sectior	
Ambient Tempurature Ir	Deg Celsius Per Section At Zero Percent Rated Power:
35.0 single section	
Power Dissipation Ratir	g Per Section In Watts:
1.5 free air single section	
Function Conformity Pe	r Section:
Single section independe	nt linearity
Resistance Tolerance P	er Section In Percent:
3.0/+3.0 single section	
Actuator Travel Control	Feature:
Stops	
Function Characteristic	Per Section:
Single section linear	
Tempurature Coefficien	t Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-0.0 to 130.0 single section	n
Ambient Tempurature Ir	Deg Celsius Per Section At Full Rated Power:
40.0 single section	
Test Data Document:	
11189-40076 drawing (thi	s is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification	n, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Qua	ntity:
3 turret	
Shelf Life:	
N/a	
Unit Of Measure:	

No

# NSN 5905-00-009-2974

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

