Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-009-3126

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

2.702 inches

#### First Flat Length:

0.344 inches

#### Flat Height:

0.216 inches

#### Body Diameter:

2.810 inches

#### Shaft Diameter:

0.250 inches

## Shaft Length:

0.875 inches

## Mounting Bushing Length:

0.375 inches

## Body Length:

1.780 inches

#### **Overall Diameter:**

3.225 inches

## Shaft Style:

Round, flatted

## Contact Arm Electrical Off Position:

Fully ccw

#### Actuator Type:

Single shaft

## Maximum Starting Torque:

48.00 inch-ounces

#### Maximum Running Torque:

4.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

## Nonturn Device Location:

At 12 oclock

## Nonturn Device Radius:

0.500 inches

## Screw Thread Diameter:

0.375 inches

# NSN 5905-00-009-3126

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

#### **Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:** 

50.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

300.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

340.0 single section

Power Dissipation Rating Per Section In Watts:

75.0 heat sink single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

#### **Test Data Document:**

81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:** 

81349-mil-r-22/7 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0