Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-009-4506

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

## Shaft Diameter:

0.115 inches

Shaft Length:

0.058 inches

- **Body Length:**
- 1.250 inches

Body Width:

#### 0.320 inches

Body Height:

# 0.320 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Lateral Distance Between Mounting Hole Centers:

1.000 inches

### Screw Thread Diameter:

0.190 inches

#### Screw Thread Series Designator:

Unf

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

1.5 megohms single section

## Rotary Actuator Travel In Angular Deg:

7920.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

## Power Dissipation Rating Per Section In Watts:

1.0 free air single section



### **Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

#### **Actuator Travel Control Feature:**

Clutch

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A002a0