NSN 5905-00-009-4532

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-009-4532 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.377 inches **Terminal Length:** 0.125 inches **Body Diameter:** 0.696 inches **Body Length:** 0.252 inches **Overall Diameter:** 0.696 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 100.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 260.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-500.0 to 900.0 single section

NSN 5905-00-009-4532

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: