

View Online at https://aerobasegroup.com/nsn/5905-00-009-6315

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

2.562 inches

#### **Body Diameter:**

1.812 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

0.812 inches

#### Mounting Bushing Length:

# 0.375 inches

**Body Length:** 

1.750 inches

#### **Overall Diameter:**

2.062 inches

## Shaft Style:

Round, slotted

### Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

2.00 inch-ounces

#### Maximum Running Torque:

2.00 inch-ounces

#### Maximum Stop Torque:

550.00 inch-ounces

#### **Nonturn Device Location:**

At 12 oclock

## Nonturn Device Radius:

0.562 inches

#### Shaft End Play:

0.005 inches

### Shaft Runout:

0.002 inches



Lateral Runout: 0.005 inches **Pilot Diameter Runout:** 0.00200 inches **Shaft Radial Play:** 0.0025 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.15 to 0.15 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a

Unit Of Measure:

---



Demilitarization:

No

Fiig:

A002a0