Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-010-0536

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

0.562 inches

#### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.375 inches

## Mounting Bushing Length:

# 0.188 inches

**Body Length:** 

0.188 inches

## **Overall Diameter:**

1.375 inches

## Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

#### Fragility Factor:

Moderately rugged

#### Screw Thread Diameter:

0.275 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# Features Provided:

Nonmetallic shaft

# **Electrical Resistance Per Section:**

1.0 kilohms single section

# NSN 5905-00-010-0536

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Rotary Actuator Travel In Angular Deg:** 

300.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0 to 50.0 single section

Power Dissipation Rating Per Section In Watts:

0.3 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 single section

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

\_ .... .

Demilitarization:

No

---

Fiig:

A002a0